

FULL ELECTRIC SELF LIFT STACKER

Basic parameters					
	1.1	Model	Item	Unit	CDD05Z
	1.2	Power type			FULL ELECTRIC
	1.3	Load capacity	Q	kg	500
	1.4	Load center	C	mm	500
	1.5	Fork outside width	W3	mm	565/685
	1.6	Fork length	L2	mm	1195
	1.7	Operator type			Walk
Wheel					
	2.1	Tire type(front/rear)			PU
	2.2	No. Of Wheel(drive wheel/bearing wheel/balance wheel)			1/2/2
	2.3	Drive wheel size		mm	Φ250×74
	2.4	Bearing wheel size		mm	φ80×60
Size					
	3.1	Lifting height	H	mm	800/900/1000/1100/1200/1300
	3.2	Mast lowered height	H1	mm	1107/1207/1307/14071507/1607
	3.3	Max. lift height when forks lift up	H2	mm	2370/2470/2570/2670/2770//2870
	3.4	Min. Fork height	H3	mm	81
	1.5	Wheelbase	L0	mm	960
	3.6	Ovearll length	L1	mm	1676
	3.7	Leg length	L3	mm	717
	3.8	Machine body thickness	L6	mm	409
	3.9	Overall width	W	mm	658
	3.10	Wheel distance(FR)	W1	mm	409/529
	3.11	Fork width	B	mm	195
	3.12	Min. Turning radius	Wa	mm	1147
Performance					
	4.1	Max. Travel speed(loaded/unloaded)		km/h	0.5/3.0
	4.2	Grade ability (loaded/unloaded)		%	5/10
Configuration					
	5.1	Driving motor		kW	DC 0.6
	5.2	Lifting motor		kW	DC 0.8
	5.3	Battery		V/Ah	48/15
	5.4	Battery type			Lithium
Weight					
	6.1	Battery weight		kg	5
	6.2	Total weight(include battery)		kg	305/310/315/320/325/330



